

DESINCRUSTADORES / MARTELETES / REBARBADORES



FC-01SA



FC-01-3



FC-1Z-1-4Z-1



FCH-20



FCH-25



FNS-2



FNS-2P



FRH-6A



FR-32



FRH-3-1

Modelo	Cinzel	Impactos Hz	Diâmetro do Pistão mm	Curso mm	Comprimento mm	Peso Kg	Consumo de Ar m <sup>3</sup> /min	Encaixe da Mangueira PT	Mangueira pol
	mm								
FC-01SA-H	12x45	50	20	44.5	273	2.50	0.42	1/4	3/8
FC-01SA-R	14x45	50	20	44.5	273	2.50	0.42	1/4	3/8
FC-01-3	12x45	50	20	45.0	273	2.60	0.42	1/4	3/8
FC-1Z-1	14.8x60	50	28	25.0	300	5.00	0.60	3/8	1/2
FC-2Z-1	14.8x60	42	28	51.0	342	5.70	0.60	3/8	1/2
FC-3Z-1	14.8x60	38	28	76.0	386	6.30	0.65	3/8	1/2
FC-4Z-1	14.8x60	28	28	102.0	424	6.80	0.65	3/8	1/2
FCH-20	-	90	20	16.0	176	0.80	0.14	1/4	1/4
FCH-25	-	60	25	20.0	204	1.50	0.18	1/4	3/8
FNS-2	-	133	25	7.0	325	1.90	0.18	1/4	3/8
FNS-2P	-	133	25	7.0	371	2.50	0.18	1/4	3/8
FRH-3-1	HEX	60	14.3	38.00	140	1.1	0.35	1/4	3/8
FRH-6-1	HEX	30	12.7	100.0	206	1.40	0.35	1/4	3/8
FRH-6A-1	HEX	50	20	44.5	193	1.50	0.40	1/4	3/8
FR-32	-	12	32	127	1086	10.0	0.80	3/8	1/2

MOTORES PNEUMÁTICOS



F-5SM-8.5R



F-5SM-2R



F-6SM-2.5R, 28R



F-8SM-12R, 28R



F-8SM-8.5R

REVERSÍVEL

Modelo	Capacidade			Potência		Velocidade Rpm	Comprimento mm	Diâmetro do Eixo mm	Peso Kg	Consumo de Ar m <sup>3</sup> /min	Encaixe da Mangueira PT	Mangueira pol
	Nm	Kg.f	ft.lb	Hp	W							
F-5SM-8.5R	5.4	0.55	4.0	0.16	118	850	147	7.0	0.50	0.28	1/8	1/4
F-5SM-2R	21.6	2.20	15.9	0.14	303	190	180	7.0	0.80	0.28	1/8	1/4
F-6SM-28R	3.3	0.34	2.5	0.34	250	2.300	146	8.5	0.80	0.34	1/8	3/8
F-6SM-21R	4.0	0.41	3.0	0.34	250	2.000	146	8.5	0.90	0.34	1/8	3/8
F-6SM-12R	5.9	0.60	4.3	0.30	221	1.000	157	8.5	0.90	0.34	1/8	3/8
F-6SM-8R	9.8	1.00	7.2	0.30	221	750	179	8.5	1.10	0.34	1/8	3/8
F-6SM-5R	14.7	1.50	10.8	0.30	221	500	179	8.5	1.10	0.34	1/8	3/8
F-6SM-2.5R	26.0	2.65	19.2	0.28	206	250	192	8.5	1.20	0.34	1/8	3/8
F-8SM-28R	6.4	0.65	4.7	0.50	368	2.300	183	12.0	1.50	0.50	1/4	3/8
F-8SM-12R	9.8	1.00	7.2	0.50	368	1.100	199	12.0	2.20	0.50	1/4	3/8
F-8SM-8.5R	14.7	1.50	10.8	0.50	368	850	222	16.0	2.40	0.50	1/4	3/8

NÃO REVERSÍVEL

Modelo	Capacidade			Potência		Velocidade Rpm	Comprimento mm	Diâmetro do Eixo mm	Peso Kg	Consumo de Ar m <sup>3</sup> /min	Encaixe da Mangueira PT	Mangueira pol
	Nm	Kg.f	ft.lb	Hp	W							
F-5SM-8.5	5.9	0.60	4.3	0.18	132	950	151	7.0	0.50	0.28	1/8	1/4
F-5SM-2	23.5	2.40	17.4	0.16	118	200	182	7.0	0.80	0.28	1/8	1/4
F-6SM-28	3.9	0.40	2.9	0.40	294	2.800	167	8.5	0.70	0.34	1/4	3/8
F-6SM-21	4.4	0.45	3.3	0.40	294	2.400	167	8.5	0.80	0.34	1/4	3/8
F-6SM-12	7.4	0.75	5.4	0.35	257	1.300	178	8.5	0.80	0.34	1/4	3/8
F-6SM-8	10.8	1.10	8.0	0.35	257	900	200	8.5	1.00	0.34	1/4	3/8
F-6SM-5	15.7	1.60	11.6	0.35	257	600	200	8.5	1.00	0.34	1/4	3/8
F-6SM-2.5	28.4	2.90	21.0	0.35	257	300	213	8.5	1.10	0.34	1/4	3/8
F-8SM-28	7.4	0.75	5.4	0.60	441	2.600	173	12.0	1.30	0.50	1/4	3/8
F-8SM-12	11.8	1.20	8.7	0.60	441	1.300	200	12.0	2.00	0.50	1/4	3/8
F-8SM-8.5	16.7	1.70	12.3	0.60	441	900	208	16.0	2.20	0.50	1/4	3/8